

Product Specifications

Pocket-Type Thermo-Hygrometer

	Humidity	Temperature
Measurement Range	20-95% RH in 59-122°F / 15-50°C range	32-122°F/0-50°C
	25-95% RH in 41-122°F / 5-50°C range	
	30-95% RH in 32-122°F / 0-50°C range	
Display Accuracy	3% RH (in 30-90% range only)	±0.9°F / ±0.5°C
Display Resolution	1%	0.1°F / C
Display Reading Update	10 seconds	
Battery Type	CR2032 coin cell or equivalent, X 1 piece	
Battery Life	About 15,000 hours	
Display Size	1.85in (W) x 0.47in (H) / 47mm (W) x 12mm (H)	
Product Size	5.12in (W) x 0.91in (H) x 0.79in (D) 130mm (W) x 23mm (H) 20mm (D)	
Product Weight	0.96oz / 27.2g (without battery)	
Certification	CE mark	



Model 13308

- Internal temperature and humidity sensors
- Dual display for temperature and humidity
- Maximum & minimum reading memory
- °F/°C selectable
- Fast reading update
- Large and clear display
- Pen shape design with a pocket clip attached to back side

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 13308 20D1

