

# Product Specifications

## FlashLink<sup>®</sup> NOW 4G/5G Real-Time In-Transit Logger

<b>Temperature Range</b>	-30°C to 70°C (-22°F to 158°F)
<b>Temperature Accuracy</b>	±0.5°C from -10°C to 45°C (±0.9°F from 14°F to 113°F), ±1.0°C (2.0°F) Other
<b>Temperature Resolution</b>	0.1°C/°F
<b>Temperature Sensor Type</b>	Internal Digital Temperature Sensor (NIST traceable)
<b>Temperature Scale</b>	Celsius
<b>Light Sensor Range</b>	0 to 52000 lux
<b>Light Detecton Accuracy</b>	0.01 lux
<b>Usage Type</b>	Single-use
<b>Data Capacity</b>	Max 28800 Readings
<b>Logging Interval</b>	10 Min.
<b>Data Upload Interval</b>	90 Min.
<b>Trip Duration</b>	70-Day (based on logging and uploading intervals)
<b>Cellular</b>	Global LTE Cat-1 for 4G/5G network, with 2G fallback
<b>SIM</b>	Internal Embedded (Global Data Roaming)
<b>Power Source</b>	Lithium-ion battery, meets UN38.3
<b>Battery Shelf Life</b>	1 year
<b>Logger Dimensions</b>	4.05in x 2.41in x 1.18in (103mm x 61.3mm x 30mm)
<b>Weight</b>	4.6 oz (130 grams)
<b>Waterproof Rating</b>	IP64
<b>Certification</b>	FCC, RoHS, NIST traceable temperature accuracy
<b>PDF Report Backup</b>	Micro USB to USB cable to download full trip PDF report



### Model 22390-05

- Next generation of global cellular communications real-time loggers with LCD using 4G/5G LTE/2G
- Precision location accuracy using latest global cellular technology with Wi-Fi triangulation positioning
- Monitors location, temperature, light
- Proactively manage shipment location and conditions to reduce the risk of product loss due to temperature excursions
- FlashTrak Cloud Service platform offers different levels of access to optimize user experience and API integration into customer systems. FlashTrak receiver program allows shippers to customize access to alerts and shipment conditions
- USB option to download PDF trip data should network not be available.
- Light sensors alert you to unplanned security access which reduces and averts potential product theft during transportation

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 22390-05 24A1

