

Product Specifications

FlashLink® Dry Ice -90°C USB PDF In-Transit Logger

| | |
|--|--|
| Measurement Range | -130°F to 113°F (-90°C to 45°C) |
| Temperature Resolution | 0.1°F/°C |
| Accuracy | ±2.7°F from -130°F to -4°F (±1.5°C from -90°C to -20°C) ±0.9°F From -4°F to 77°F (±0.5°C from -20°C to 25°C) ±2.7°F from 77°F to 113°F (±1.5°C from 25°C to 45°C) |
| Data Capacity | 32,000 data points |
| Data Download Time | 5 seconds |
| Factory Programmable Alarm Levels | High/low limits over entire temperature range |
| Operating Life | 30-days with continuous exposure to dry ice at or below -80°C 5-days with continuous exposure at -90°C |
| Battery | One ½ AA, 3.6 volts |
| Dimensions | 1.57in x 3.67in x 0.94in (40mm x 93.5mm x 24mm) |
| Casing | ABS plastic |
| Weight | 1.9 oz (54 grams) |
| Shock Resistance | Withstands 3-foot (1 meter) drop to hard surface |
| Certification | Calibration traceable to NIST, ROHS Compliant, BSS 7061 Compliant, CE Mark |
| Display | LCD, RED LED Alarm |
| Storage Conditions | -4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation |
| PDF Standards | Complies with ISO19005-1, PDF/A, 21 CFR Part 11 |
| System Requirements | Windows PC with current operating system, Adobe Reader |
| Download Requirements | Direct USB connection |

Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system



Pillow Sleeve



| Model | 40800 | 40801 |
|--------------------------|--------|--------|
| Temperature Scale | °F | °C |
| Sample Rate | 10 Min | 10 Min |

- Ideal for storage and transport with dry ice
- Compact, single-use in-transit temperature logger
- Onboard software automatically creates a PDF report and CSV file
- Trip history statistics available on LCD
- Patented Shadow Log® feature guarantees data even if the operator fails to start the unit
- Direct USB connection, no cradle, reader or adapter needed
- Meets IATA Dangerous Goods Regulations

SS 40800-X 24CI

